

IMAGEPROGRAF W imagePROGRAF iPF785/780/685/680





TECHNICAL DOCUMENTS

LARGE-FORMAT PRINTING



These printers aim to boost productivity while staying true to some of their great legacy features. Faster draft printing, increased ink tank sizes, a new magenta ink, and software enhancements help make printing easier and more convenient than ever before, while the sub-ink-tank system, large on-board hard drive,* and user-friendly assembly all carry over to help ensure the printer operates seamlessly into your workflow.

NEW FEATURES

HIGH PRODUCTIVITY

• **Print speeds** are capable of producing a 24" x 36" Arch D-sized print in approximately **21 seconds** in Economy Mode!

LARGE-CAPACITY INK TANKS

 In addition to the 130 ml ink tanks, 300 ml ink tanks are compatible with these solutions to **help lower ink costs** per print. Users also have the option to mix and match ink tank sizes.

NEW MAGENTA INK

• A newly formulated Magenta ink helps improve the **clarity and vibrancy** of red fine lines, text, and images.

SUB-INK-TANK SYSTEM

 Allows for ink tanks to be changed on the fly, without interrupting the print job.

SOFTWARE

• Canon workflow solutions feature familiar and new favorites, such as a new mobile printing app, ^^ Direct Print & Share, Status Monitor, Media Configuration Tool, Print Plug-in for Microsoft® Office, and more!

[▲]iPF785/780 models only.

App can be downloaded from iTunes®.

image**PROGRAF**


ADVANTAGES

SPEED

The iPF785/780 and iPF685/680 printers offer speeds that have never been seen before on previous Canon imagePROGRAF large-format printer models. In their fastest mode (Economy Mode), the 36" iPF785/780 printers are capable of reproducing 24" x 36" Arch D-sized prints in approximately **21 seconds!** The 24" iPF685/680 printers can reproduce 24" x 36" Arch D-sized prints in approximately 25 seconds!

INK

A newly formulated Magenta ink helps improve the clarity and **vibrancy** of red fine lines, text, and images in many technical and poster prints. The color gamut has also increased in the orange to red areas when compared to previous models. From a productivity perspective, the printers now support ink tank sizes of 300 ml to help lower the cost per print. The included sub-ink-tank system allows for users to use all the ink that's available in a tank before replacement is needed. It also allows for on-the-fly swapping of ink tanks, should one run out during the middle of a print job.



ADDED FEATURES

All four models include the flat stacker/basket, previously seen on only the iPF76x Series models. This feature provides the capability to neatly stack up to twenty 24" x 36" plain paper prints and can be enabled or disabled based on user preference.

* Available at the App Store. Compatible with iPad® 2 or later, running iOS 6.1 or later. Data charges may apply. Printed output will be the same size as original file. Mobile device and large-format printer must utilize the same network. Printer must be connected to the same router that the mobile device is connected to via wireless capability. Wireless performance may vary based on terrain and distance between the printer and wireless network clients. In order to print from imagePROGRAF Print Utility, user must open his/her PDF file in another, supported iPad app. Then, the user would select "Open In" and choose the Print Utility app.

Also included on the iPF785 and iPF685 models is a 320 GB hard drive, allowing for the storage of up to 500 print jobs, the creation of individual user mail boxes, and improved print processing while falling under U.S. Department of Defense requirements (DoD 5220.22-M).

SOFTWARE

Enhancements to the line-up of imagePROGRAF software solutions will help improve printing workflow and management.

imagePROGRAF Print Utility*

For the first time, a mobile app has been made available for imagePROGRAF large-format printers. This iOS-based app allows users to print PDF files from their iPad®.

Direct Print & Share 2.0**

Canon's cloud-based portal solution has been updated to support additional WebDAV-compliant cloud servers, along with HP-GL/2 data to allow for the printing of JPG, TIFF, PDF, and HP-GL/2 files from almost anywhere in the world! Also, a new "shortcut print" button has been added. With this additional functionality, hot folders can be created and set up on your desktop. You can drag and drop your files into the folders and your jobs will begin printing automatically! Multiple folders can be set up for shortcut printing, each with their own print settings for custom printing applications!

PosterArtist

Canon's optional, added-value poster-creation software has been upgraded for use with Direct Print & Share. Various software improvements with variable data printing and file structure have also been made for easier use.

Status Monitor

This software can be used with all imagePROGRAF devices and has been updated to include an "ink purchase notification" function. This notifies users when their ink supply is low and a purchase is needed.

**Your server must be compatible with a WebDAV-enabled cloud account, including, but not limited to, Google, Carbonite, or Rackspace to take advantage of the cloud functionality. Storage capacity, and any pricing thereof, is based on the third-party cloud provider's current offering, at its sole discretion. Your cloud account is subject to the third-party cloud provider's terms and conditions. Neither Canon Inc. nor Canon U.S.A., Inc. represents or warrants any third-party product, service, or feature referenced hereunder.

image**PROGRAF**



Operational Environment

PosterArtist

User-Replaceable Items

MBK, BK, C, M, Y)

Print-Head (PF-04)

59 – 86 F° (15 – 30 C°)

Relative Humidity 10 – 80% (No Condensation)

Printer Dimensions (H × W × D) and Weight with Stand and Basket iPF785/iPF780: 42" x 51" x 35" (1066.8 mm x1422.4 mm x 889 mm) with Basket Open 42" x 51" x 43" (1066.8 mm x

Extended for Flatbed Stacking
Approx. 150 lb. (68 kg)
iPF685/iPF680: 42" x 39" x 35" (1066.8 mm x 990.6 mm
x 889 mm) with Basket Open

Flatbed Stacking Approx. 125 lb. (56 kg)

Package Dimensions (H × W × D) and Weight iPF785/iPF780: 31" × 56" × 46" (787.4 mm × 1422.4 mm × 1117.6 mm)

Approx. 249 lb. (112 kg) iPF685/iPF680: 45" x 44" x 35" (1143 mm x 1117.6 mm x 889 mm)

Approx. 205 lb. (92 kg)

Ink Tank (PFI-107 MBK, BK, C, M, Y) (PFI-207

Line accuracy repeatability is guaranteed after a user

performs necessary adjustment and under the same

drawing (Plain Paper, Coated Paper, CAD Translucent

environmental conditions. Applies to media for line

The maximum printable length varies, depending on

For imagePROGRAF Printer Driver. For printing from

PostScript applications such as Adobe Illustrator or

RIP package. For a list of Canon recommended RIP

Learn more about the ENERGY STAR®

program at www.ENERGYSTAR.gov.

Canon

CANON SOLUTIONS AMERICA

Canon Solutions America, Inc. One Canon Park

Melville, NY 11747

1.800.815.4000 csa.canon.com

QuarkXPress, please use a PostScript compatible

packages, please consult with Canon Alliance and

Industry Market program list of RIP vendors at

iPF785/iPF780: Roll Holder Set (RH2-33)

iPF685/iPF680: Roll Holder Set (RH2-26)

Maintenance Cartridge (MC-10)

Matte Film, and CAD Tracing Paper) only.

Theoretical value based on data resolution

the application, OS, and RIP used.

www.usa.canon.com

1422.4 mm x 1092.2 mm) with Basket

42" x 39" x 43" (1066.8 mm x 990.6 mm x 1092.2 mm) with Basket Extended for

Temperature

Print-Head PF-04

TechnologyFINE (Full-Photolithography Inkjet Nozzle Engineering)

Print Resolution (Max.)

2400 × 1200 dpi

Line Accuracy* ±0.1% or Less

Minimum Line Weight**

0.02 mm

Number of Nozzles

Matte Black: 5,120 Nozzles

Other Colors: 2,560 Nozzles per Color

Droplet Size

4 Picoliter

Nozzle Pitch (Head Resolution)

1200 dpi × Two Rows **Print-Head Swath**

1.07 inch

Ink Type

Dye

Cyan (C), Magenta (M), Yellow (Y), Black (K)

Pigment

Matte Black (MBK)

Ink Tank

PFI-107: C, M, Y, BK, MBK PFI-207: C, M, Y, BK, MBK

Ink Tank Capacity
Starter: 130 ml (MBK), 90 ml (All other colors)

Replacement: 130 ml or 300 ml

Ink Supply Method

Tubing System with Sub-Ink-Tanks for Continuous

Ink Supply

Nozzle Recovery System

Non-firing Nozzle Detection and Compensation

Printer Controller

L-COA Processor

Printer Memory 256 MB

Hard Drive (iPF785/iPF685 only)

320 GB

32 GB Dedicated File Processing Memory

Mail Boxes (User Job Storage) (iPF785/iPF685 only)
1 Common Inbox. 29 User Inboxes

(Password-protected)

Roll Feed

One Roll, Top-loading, Front Output

Cut Sheet

One Sheet, Top-loading, Front Output

Media Width

Roll Feed iPF785/iPF780: 10" - 36" (254 mm - 914 mm)

iPF685/iPF680: 10" - 24" (254 mm - 610 mm)

Cut Sheet

iPF785/iPF780: 8" – 36" (203.2 mm – 914 mm)

iPF685/iPF680: 8" - 24" (203.2 mm - 610 mm) Printable Margins

Roll Feed

All Sides: 0.12" (3 mm) or 0" for Borderless

Cut Sheet

Leading, Sides (Left and Right): 0.12" (3 mm)

Trailing: 0.91" (23 mm) Maximum Print Length (Single Page)***

59' (18 m)

Cut Sheet 63" (1.6 m)

CSA-7/14-143

0814-CSAiPF78X/68X-PDF-IH

Borderless Printing Widths (Roll Media Only) 10", B4, A3, 14", A2, 17", B2, A1, 24"

iPF785/iPF780 only: B1, A0, 36"

Media Cutter

Durable Dual-blade Rotary Cutter

Media Thickness 0.07 = 0.8 mm (2.8 = 31.4 mil)

Media Core Sizes 2" and 3" Core (Adapter Included)

Maximum Roll Outer Diameter

5.9" (150 mm)

Output Media Bin

Flat Stacker/Basket

Output Media Bin Capacity 20 Sheets (With Stackable Configuration)

Printing Software

imagePROGRAF Printer Driver for Windows®/Mac, ImagePNOGRAP Printer Driver for Windows/Mac, Printer Driver Extra Kit for Windows/Mac (Free Layout, Color imageRUNNER® Enlargement Copy, Advanced Preview), Print Plug-in for Microsoft Office (PC only), Optimized Module for AutoCAD® for Windows, Direct Print & Share (PC Only), Status Monitor for Windows, PrintMonitor for Mac, Media Configuration Tool, PosterArtist Lite for Windows

Operating System[†]
Windows XP (32 bit), Server 2003 (32/64 bit),
Server 2008 (32/64 bit), Server 2012 (64 bit),

Windows Vista® (32/64 bit), Windows 7 (32/64 bit), Windows 8 (32/64 bit), Macintosh OS X 10.6.8 - 10.9X

GARO (Canon Proprietary), HP-GL/2, HP RTL

Interface USB 2.0 Hi-Speed, 10/100/1000Base-T/TX

Protocol

TCP/IP (IPv4/IPv6), IPX/SPX, AppleTalk®, SNMP

(Canon MIB supported), HTTP

Acoustic Noise

Operation

iPF785/iPF780: Approx. 48 dB

iPF685/iPF680: Approx. 47 dB

Standby

35dB or Less

Acoustic Power

iPF785/iPF780: Approx. 6.5 Bels iPF685/iPF680: Approx. 6.4 Bels

Power Supply AC 100–240 V (50-60 Hz)

Power Consumption

Maximum

140 W or Less

Standby 5 W or Less

Power Off

1 W or Less (Executive Order Compliant)

Certifications

Electrical Safety Regulations

TUV (USA), cTŬV (USA), TUV.S mark, CB certification (Others)

Electromagnetic Interface Regulations

FCC Class B (USA), IC Class B (Canada)

Environmental Certifications ENERGY STAR® (Worldwide), RoHS

Directive

When selecting and implementing new technology, a highly skilled technical team and services for your organization. Our team of technical professionals draws upon decades of technical expertise and real-world experience to ensure you obtain the

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has qualified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Canon, imagePROGRAF, imageRUNNER, and the GENUINE logo are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. Apple, iTunes, and iPad are registered trademarks of Apple Inc. All other referenced product names and marks are trademarks of their respective owners. All printer output images are simulated. Specifications and availability subject to change without notice. Not responsible for typographical errors. ©2014 Canon U.S.A., Inc. All rights reserved.









Utilize the imagePROGRAF iPF785/780/765/760 to its full potential with professional services from Canon Solutions America

maximum benefit from your technology investment.

